

No More Gaps® Ezi Press™ Multipurpose

Description

No More Gaps® Ezi Press™ Multipurpose is ready to use – simply press the lever to apply – no caulking gun required. High flex gap filler with a smooth finish, superior flexibility and low shrinkage to resist reappearance of cracks

Product Information

Packaging	Size	Colour
Ezi Press	170 grams	White

Uses

Use No More Gaps® Ezi Press™ Multipurpose for architraves, cornices, cabinets, cupboards, skirting boards, wall joints, windows and door frames. It is suitable for use on materials such as aluminium, brick, cement sheeting, ceramic tiles, glass, masonry, particle board, plasterboard and wood.

Technical Features

- No caulking gun required
- Easy to hold and use
- Superior flexibility
- Precision application
- Paintable
- Durable
- Flawless Finish

Technical Details

Property	Typical Result
Appearance	Thixotropic paste
Colour	White
Technology	Water evaporation
Skin Formation	7 minutes
Joint Movement	+/- 12.5%
Flow/Sag/Slump	<2mm (ISO 7390)
Shore A Hardness	30 (DIN 53505)
Elongation at Break	240% (DIN 53504)
Tensile Strength	04.MPa (DIN53504)

Indicative data only, not intended for preparation of specifications

How To Use

Application

1. Surfaces must be clean and dry
2. Remove tab lock, twist collar clockwise to MAX, remove nozzle cap, press lever to dispense.
3. Smooth with wet spatula. Clean up with water. Twist collar back to MIN and replace nozzle cap.
4. Allow 3 hours before painting. Allow longer in colder weather or for solvent-based paints.

Clean Up

Uncured product may be removed with water. Cured product can be removed by scraping or sanding.

Handy Hints

- Store in cool, dry conditions between 5°C and 25°C. Use within 6 months of purchase

Limitations

- Not suitable for Wet Areas, use **Wet Area Ezi Press™**

Warnings, First Aid and Shipping Information

This information can be located on the SDS found on the Selleys website – www.selleys.com.au or www.selleys.co.nz