

Plastic Wood

Updated 11/10/2010

DESCRIPTION

Plastic Wood is a fast-setting solvent based interior wood filling cement suitable for all types of woodwork.

SIZES AVAILABLE

Plastic Wood is available in a 50g tube and also 230g and 460g tins, tan (maple) in colour only.

USES

Selleys Plastic Wood is ideal for filling holes, dents and chips in natural wood.

TECHNICAL FEATURES

- Fast setting.
- Can be sanded, nailed, planed, painted or lacquered.
- Sets to a hard finish.
- Can be treated in all respects as real wood by staining, varnishing or painting.

TECHNICAL DETAILS	
Appearance:	Maple coloured paste.
Viscosity:	2500P (at 25℃).
Shear	1000kPa (on marine
Strength:	coachwood).

HOW TO USE

Surface must be clean, dry and free from loose material. Apply with a putty knife. Slightly overfill deep holes to allow for sanding. Do not fill more than 6mm in each application. Allow to dry before sanding, staining or painting. Replace lid firmly after use and store in a cool place.

Clean Up:

Putty knife can be cleaned with Methylated Spirits.



Plastic Wood is not flexible. Use Selleys No More Gaps for filling gaps between surfaces where structural movement occurs. Not suitable for exterior use.

WARNINGS/FIRST AID & SHIPPING

INFORMATION: Refer to the **MSDS** section located on the Selleys Website.



© 2010 Selleys Pty Limited ABN 67 000 049 427

Ph: AU - 1300 555 205 Ph: NZ - 0800 735 539 Website - www.selleys.com.au Email - selleys.customer.service@selleys.com.au Head Office: 1 Gow Street, Padstow NSW 2211 AU



All information contained in this Product Information Sheet is as accurate and up-to-date as possible. Products can be expected to perform as indicated in this Sheet, so long as application procedures are followed as recommended. However, there are no expressed or implied warranties set out in this information other than those implied by Commonwealth, State or Territory Legislation.