

Wet Area Ezi Press[™]

Description

Wet Area Ezi Press[™] is ready to use – simply press the lever to apply – no caulking gun required. It provides a superior waterproof seal and resistance to unsightly mould – ideal for wet areas like bathrooms and kitchens

Product Information

Packaging	Size	Colour
Ezi Press	100 grams	White
Ezi Press	100 grams	Clear

Uses

Wet Area Ezi Press[™] is ideal for use on or around showers, baths, spas, plumbing fixtures and sinks. It will work on materials such as ceramic, glazed & porcelain fixtures, metal, copper & brass fittings, powder coated aluminium, aluminium, plastic laminates, rubber, glass, stainless steel and concrete.

Technical Features

- No caulking gun required
- Easy to hold and use
- Superior waterproof seal
- Will not shrink crack or peel away
- Mould resistant

Technical Details

Property	Typical Result
Technology	Neutral cure silicone sealant
Curing Rate	2mm Per Day
Skin Time	5-10 Minutes (Weather dependent)
Joint Movement Capability	+/- 25%
Technology	Neutral cure silicone sealant
Flo/Sag/Slump	< 2mm (ISO 7390)
Shore A Hardness	16 (DIN 53505)
Elongation at Break	500% (DIN 53504)
Tensile Strength	1.22MPa (DIN 53504)

Indicative data only, not intended for preparation of specifications

How To Use

Directions

Use in a well ventilated area. Avoid contact with skin and eyes.

Application

1. Clean and dry surface using mineral turpentine.
2. Remove tab lock, twist collar clockwise to MAX, remove nozzle cap, press lever to dispense.
3. Smooth with a spatula dipped in soapy water. Clean up before sealant skins (5-10 minutes) with a cloth dampened in mineral turpentine. Twist collar back to MIN and replace nozzle cap
4. Sealant will fully cure in 72 hours

Clean Up

Uncured product may be removed with mineral turpentine. Cured product can be removed with Selleys Silicone Remover or by cutting and scraping.

Handy Hints

- For neater joints, mask sides before applying sealant and remove tape before sealant skins.
- Keep sealant cleaned regularly to avoid build-up of soap scum. Use **Selleys[®] Soap Scum Buster[™]** or **Selleys[®] Rapid Mould Killer[™]**
- Store in a cool dry place between 5°C and 25°C.
- Use within 6 months of opening

Limitations

- Not paintable. Complete painting 7 days prior to applying sealant
- Not suitable for aquariums
- Not Suitable for food, eating utensils or drinking water contact

Warnings, First Aid and Shipping Information

This information can be located on the SDS found on the Selleys website – www.selleys.com.au or www.selleys.co.nz