

# 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: FLEXISEAL SEA

 Synonyms
 Product Code
 Bar Code

 Flexiseal SEA 310 ml White
 9300697130402

 Flexiseal SEA 310 ml Black
 9300697130419

 Flexiseal SEA 310 ml Grey
 9300697130426

 Flexiseal SEA 600 ml White
 9300697130464

 Flexiseal SEA 600 ml Grey
 9300697130471

 Flexiseal SEA 600 ml Black
 9300697130488

Recommended use: Sealant

**Supplier:** Nippon Paint (Singapore) Co. Pte Ltd **Street Address:** 1 First Lok Yang Road, Jurong

Singapore 629728

**Telephone:** +65 6265 5355

Emergency Telephone number: +613 9663 2130

# 2. HAZARDS IDENTIFICATION

This material is hazardous according to Singapore Standard SS 586: 2014.



# Signal Word

Danger

## **Hazard Classifications**

Eye Damage/Irritation - Category 2A Sensitisation - Respiratory - Category 1

# **Hazard Statements**

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# **Prevention Precautionary Statements**

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P264 Wash hands, face and all exposed skin thoroughly after handling.

P280 Wear protective gloves/protective clothing including eye/face protection and suitable

respirator.

P284 In case of inadequate ventilation wear respiratory protection.

# **Response Precautionary Statements**

P101 If medical advice is needed, have product container or label at hand.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

Product Name: FLEXISEAL SEA Reference No: SELSGPEN001062
Issued: 2021-04-29 Version: 1.0 Page 1 of 7



position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

#### **Storage Precautionary Statement**

Not allocated

#### **Disposal Precautionary Statement**

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

#### DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the United Nations "Recommendations on the Transport of Dangerous Goods."

# 3. COMPOSITION INFORMATION CHEMICAL ENTITY CAS NO

 Xylene
 1330-20-7
 1 -< 5 % (w/w)</td>

 4, 4' - diphenylmethane diisocyanate (MDI)
 101-68-8
 <1 % (w/w)</td>

 Silane, trimethoxy[3-(oxiranylmethoxy)propyl] 2530-83-8
 <1 % (w/w)</td>

Ingredients determined to be Non-Hazardous - Balance

100%

**PROPORTION** 

# 4. FIRST AID MEASURES

**Inhalation:** Effects may be delayed. Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

**Skin Contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

**Eye contact:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**PPE for First Aiders:** Wear safety shoes, overalls, gloves, chemical goggles, air mask. Use with adequate ventilation. If inhalation risk exists, wear air-supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated

Product Name: FLEXISEAL SEA Reference No: SELSGPEN001062
Issued: 2021-04-29 Version: 1.0 Page 2 of 7



clothing and other protective equipment before storing or re-using.

**Notes to physician:** Treat symptomatically. Effects may be delayed.

#### 5. FIRE FIGHTING MEASURES

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

**Fire fighting further advice:** On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

# **6. ACCIDENTAL RELEASE MEASURES**

#### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

#### LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

# 7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# National occupational exposure limits:

|                                      | PEL (Long Term)<br>ppm mg/m3 |       | PEL (Short Term)<br>ppm mg/m3 |     | NOTICES |
|--------------------------------------|------------------------------|-------|-------------------------------|-----|---------|
| Methylene bisphenyl isocyanate (MDI) | 0.005                        | 0.051 | -                             | -   | -       |
| Xylene                               | 100                          | 434   | 150                           | 651 |         |

As published in the Workplace Safety and Health (General Provisions) Regulations, 2006.

Product Name: FLEXISEAL SEA Reference No: SELSGPEN001062
Issued: 2021-04-29 Version: 1.0 Page 3 of 7



PEL (Long Term) - the permissible exposure level over an 8-hour working day and a 40-hour work week.

PEL (Short Term) - the permissible exposure level over a 15-minute period during any working day.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the Workplace Health and Safety Guidelines – Statutory Medical Examinations, 2011 the ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Avoid generating and inhaling dusts. Use with local exhaust ventilation or while wearing dust mask.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, AIR MASK.

# MANUFACTURING, PACKAGING AND TRANSPORT:

Wear safety shoes, overalls, gloves, chemical goggles, air mask. Use with adequate ventilation. If inhalation risk exists, wear air-supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

#### RECOMMENDATIONS FOR CONSUMER USE:

Wear safety glasses and gloves. Avoid inhaling vapours.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Paste

Colour: Various colours
Odour: Characteristic

Solubility: N Av

**Density:** 1.17 - 1.23 g/mL

Relative Vapour Density (air=1): N Av Vapour Pressure (20 °C): N Av Flash Point (°C): N App Flammability Limits (%): N App Autoignition Temperature (°C): N App Melting Point/Range (°C): N Av Boiling Point/Range (°C): N Av N Av pH:

Product Name: FLEXISEAL SEA Reference No: SELSGPEN001062

Issued: 2021-04-29 Version: 1.0 Page 4 of 7



N Av Viscosity: Total VOC (g/Litre): 80

> (Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

# 10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

# 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

## **Acute Effects**

Inhalation: Material may be an irritant to mucous membranes and respiratory tract. A respiratory sensitiser. Can cause possible allergic reactions.

**Skin contact:** Contact with skin may result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

# **Acute toxicity**

Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >5 mg/L

Skin contact: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

Ingestion: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as a Category 1 Hazard (respiratory sensitiser). Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

**Product Name: FLEXISEAL SEA** Reference No: SELSGPEN001062 Issued: 2021-04-29

Version: 1.0

Page 5 of 7



Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

**Chronic Toxicity** 

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

# 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log  $K_{ow}$  < 4.

**Ecotoxicity:** No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

# 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

# 14. TRANSPORT INFORMATION

# **ROAD AND RAIL TRANSPORT**

Not classified as Dangerous Goods by the criteria of the United Nations "Recommendations on the Transport of Dangerous Goods."

# MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

### AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous

Product Name: FLEXISEAL SEA Reference No: SELSGPEN001062
Issued: 2021-04-29 Version: 1.0 Page 6 of 7



Goods Regulations for transport by air.

#### 15. REGULATORY INFORMATION

# This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent) Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

# This material/constituent(s) is covered by the following requirements:

- Environmental Protection and Management Act (isocyanates)
- Environmental Protection and Management (Hazardous Substances) Regulations
- Workplace Safety and Health (General Provisions) Regulations

# Environmental Protection and Management (Hazardous Substances) Regulations

#### Ingredient names

#### **Control Quantity**

4, 4' - diphenylmethane diisocyanate 500 kg (MDI)

# 16. OTHER INFORMATION

Reason for issue: First Issue

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

**Product Name: FLEXISEAL SEA** Reference No: SELSGPEN001062 Issued: 2021-04-29 Page 7 of 7

Version: 1.0