

No More Gaps® Coloured Caulk

Description

No More Gaps® Coloured Caulk is specially formulated to provide the best gap protection and a smooth finish to suit a large range of surfaces

Product Information

Packaging	Size	Colour
Cartridge	450 grams	White
Cartridge	450 grams	Brilliant White
Cartridge	450 grams	Baked Earth
Cartridge	450 grams	Black
Cartridge	450 grams	Brown
Cartridge	450 grams	Cedar
Cartridge	450 grams	Charcoal
Cartridge	450 grams	Coffee
Cartridge	450 grams	Cream
Cartridge	450 grams	Ivory
Cartridge	450 grams	Light Grey
Cartridge	450 grams	Rich Earth
Cartridge	450 grams	Terracotta
Cartridge	450 grams	Vanilla

Uses

Use No More Gaps® Coloured Caulk for sealing gaps and joints where colour matching and enhancement is required around window and door frames, cabinets, cupboards, bathrooms, kitchens, architraves and skirting, bench tops and tiles. It is suitable for materials such as timber, masonry, plasterboard, Colourbond®, cement sheeting, particle board, brick, ceramic tiles, glass and aluminium.

Technical Features

- Excellent Flexibility
- Easy Colour matching
- Interior and Exterior
- Mould and mildew resistant
- Water clean up
- Maximum durability
- Paintable with water and oil based paints

Technical Details

Property	Typical Result
Appearance	Smooth paste
Technology	Water Evaporation
Skin time	20 minutes*
Flow/sag/slump	Less than 2mm (MII-S-8802E)
Shore A Hardness	Greater than 40
Ultimate Tensile Strength	0.6MPa (ASTM D412)
Peel Strength (ASTM D412)	5kgcm-1 (Anodised Aluminium)
Joint Movement Capability	Up to +/- 20% (ISO 9046)
Maximum Elongation	Greater than 350% (ASTM D412)

Indicative data only, not intended for preparation of specifications

How To Use

Application

1. Surface must be clean, dry and free from dust, grease, flaking / powdery paint and old or crumbling caulk.
2. Cut tip off cartridge and cut nozzle. Fit nozzle to cartridge. Place cartridge into caulking gun.
3. Apply with caulking gun, forcing product into gap.
4. Smooth with a wet finger/spatula
5. Clean up with a damp cloth immediately.
6. Allow surfaces to skin prior to painting
7. Avoid water contact until cured – 72 hours or longer in cold weather.

Clean Up

Uncured product may be removed with water. Cured product can be removed by sanding and scraping

Handy Hints

- Do not apply or store below 5°C

Limitations

- Not recommend for foot traffic areas

No More Gaps[®] Coloured Caulk

- Not recommended for gaps between tongue and groove boards and weatherboards, use **No More Gaps[®] Exterior & Weatherboard**
- Not for areas in prolonged contact with water e.g. showers, pools and spas.
- Where significant joint movement is occurs or for areas of frequent immersion use the appropriate **Selleys[®] Silicone Sealants**

Warnings, First Aid and Shipping Information

This information can be located on the SDS found on the Selleys website – www.selleys.com.au or www.selleys.co.nz